

Features

- Two sort trays
- Throughput speeds of up to 85 pages per minute (PPM)
- Duplex camera imaging at 50 to 600 DPI output resolution
- Ultrasonic multi-feed detection
- Document Imprinter, post image (front standard; rear optional)
- Color Dropout
- Mixed document scanning
- Bi-tonal, grayscale and color scanning
- Left-justified feeding
- User-friendly touch screen control*



Software Options

- SoftTrac® ScanDS - for non-sort applications
- SoftTrac ScanDS Sort Add-on - for intelligent sort applications
- ImageTracDS software bundles
- SoftTrac Capture Suite - additional modules
- DocNetics®
- SoftTrac Synergetics
- Connectors for Kofax Capture, TiS eFlow, EMC Captiva

SCANNER FEATURES			
DUAL OUTPUT TRAYS			
# 1 - 300 sheets # 2 - 100 sheets			
FEEDER TRAY (ADF)			
300 sheets – left-justified feeder			
MULTI-FEED DETECTION			
Ultrasonic			
DOCUMENT IMPRINTER - SINGLE HEAD, POST IMAGE			
Front standard, 38 characters max. Rear add-on available as an option.			
ILLUMINATION			
LED			
PAPER SIZE	MAXIMUM	SORT	11.7 inches x 12 inches
		NO SORT	24.8 inches x 12 inches
	MINIMUM	2.8 inches x 1.9 inches	
PAPER THICKNESS			
41 – 174 g/m2 (11 – 46 lbs)			
DUTY CYCLE			
85,000 pages per day			
SUPPORTED DRIVERS			
TWAIN			
IMAGE CAPTURE & OUTPUT			
SIMPLEX AND DUPLEX CAPTURE			
24 bit color			
RESOLUTION	OPTICAL	600 dpi	
	OUTPUT	50 – 600 dpi. Bitonal, Grayscale, Color	
FILE FORMAT OUTPUT			
JPEG, TIFF			
COLOR DROPOUT			
Single color - red, green or blue All colors - (only black remains) Custom - user defined			
THROUGHPUT - PPM**			
Up to 85 PPM		**approx. PPM for 8.5 x11 at 200 or 300 dpi, landscape orientation	

*Requires touch-screen monitor, sold separately

PC AND OPERATING SYSTEM REQUIREMENTS	
CPU	Intel processor, 3.4 GHz, Core i7 2600 or above
MEMORY	4 GB 1333 MHz or faster
UNUSED HARD DISK SPACE	10 GB or more
INTERFACE	USB 3.0 Port on PCIe, Gen 2 Slot or equivalent embedded on motherboard - Directly connect the device to the PC. Connection through a USB HUB is not supported. - Use the USB cable (For 3.0) inside the package sent with the device. Use of other cables may not guarantee maximum performance.
SUPPORTED OPERATING SYSTEM	Windows® 7 Professional, 64 bit, Windows® 8.1 Professional, 64 bit
CERTIFICATIONS	
SAFETY	IEC/EN 60950-1:2005 (Second Edition), UL 60950-1:2007, CAN/CSA-C22.2 No. 60950-1-07
EMISSIONS	CISPR22(2003): [EN55022(2006)A1(2007) Class A, EN61000-3-2(2006), EN61000-3-3(2008), EN55024(1998)A1(2001)A2(2003), ICES-003 Issue.4(2004.2)], FCC Part 15.107 (2008.7) Class A, FCC Part 15.109 (2008.7) Class A,
ADDITIONAL INFORMATION	
DIMENSIONS	21 inches L x 16.1 inches W x 16.5 inches H
WEIGHT	46.3 lb / 21 kg
POWER REQUIREMENTS	100 – 240VAC, 1.0A, 50/60Hz
ACOUSTICAL NOISE	Operating Mode = 58 dB; Standby Mode = 45 dB
ENVIRONMENTAL FACTORS	RoHS2 Directive 2011/65/EU-EN50581, Energy Star
OPERATING TEMPERATURES	50 to 95 degrees (F), 10 to 35 degrees (C)
OPERATING HUMIDITY	35% to 70% non-condensing (percent relative humidity)
SHIPPING/STORAGE TEMPERATURES	-14 to 109 degrees (F), -10 to 43 degrees (C)